

View Online at <https://aerobasegroup.com/nsn/5306-01-437-2652>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.902 inches

Fastener Length:

Between 6.637 inches and 6.657 inches

Head Style:

Dished hexagon

Head Height:

Between 0.297 inches and 0.327 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 5.740 inches and 5.760 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

32.0 microinches threads

Material:

Steel comp 4340 and steel comp 8740

Material Specification:

II-s-5000 federal specification 10th material response and il-6049 federal standard 10th material response

Surface Treatment:

Chromate and cadmium

Surface Treatment Specification:

Qq-p-416, ty2cl2 federal specification 1st treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6610 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0