

View Online at <https://aerobasegroup.com/nsn/5306-01-437-2653>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.095 inches and 1.155 inches

**Shank Length:**

Between 1.095 inches and 1.155 inches

**Eye Stock Diameter:**

Between 2.620 inches and 2.640 inches

**Shoulder Diameter:**

Between 0.993 inches and 0.998 inches

**Shoulder Length:**

Between 2.090 inches and 3.010 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Ring Stock Diameter:**

Between 2.253 inches and 2.273 inches

**Thread Diameter:**

0.750 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Threaded End To Shank Hole Center:**

0.241 inches first hole and 0.251 inches first hole

**Material:**

Steel comp 4340 or steel comp 4140 or steel comp 8735 or steel comp 8740

**Surface Treatment:**

Cadmium and chromate or zinc

**Surface Treatment Specification:**

Qq-p-416, ty2cl3 federal specification 1st treatment response or qq-p-325, ty2, cl3 federal specification 2nd treatment response

**Style Designator:**

Swivel

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1251 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0