

View Online at <https://aerobasegroup.com/nsn/5306-01-437-2653>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.095 inches and 1.155 inches

Shank Length:

Between 1.095 inches and 1.155 inches

Eye Stock Diameter:

Between 2.620 inches and 2.640 inches

Shoulder Diameter:

Between 0.993 inches and 0.998 inches

Shoulder Length:

Between 2.090 inches and 3.010 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Ring Stock Diameter:

Between 2.253 inches and 2.273 inches

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Threaded End To Shank Hole Center:

0.241 inches first hole and 0.251 inches first hole

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8735 or steel comp 8740

Surface Treatment:

Cadmium and chromate or zinc

Surface Treatment Specification:

Qq-p-416, ty2cl3 federal specification 1st treatment response or qq-p-325, ty2, cl3 federal specification 2nd treatment response

Style Designator:

Swivel

Thread Series Designator:

Unjf

Specification Data:

80205-nas1251 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0