

View Online at <https://aerobasegroup.com/nsn/5306-01-437-3247>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.995 inches and 1.155 inches

Shank Length:

Between 0.955 inches and 1.155 inches

Eye Stock Diameter:

Between 0.667 inches and 0.707 inches

Shoulder Diameter:

Between 0.993 inches and 0.998 inches

Shoulder Length:

2.375 inches

Ring Stock Diameter:

Between 0.667 inches and 0.707 inches

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4340 and steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-8503 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response

Surface Treatment:

Cadmium and chromate or zinc

Surface Treatment Specification:

Qq-p-416 ty2cl3 federal specification 1st treatment response or qq-p-325 ty2cl3 federal specification 2nd treatment response

Style Designator:

Swivel

Thread Series Designator:

Unjf

Specification Data:

80205-nas1251 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.