

View Online at <https://aerobasegroup.com/nsn/5306-01-437-3247>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.995 inches and 1.155 inches

**Shank Length:**

Between 0.955 inches and 1.155 inches

**Eye Stock Diameter:**

Between 0.667 inches and 0.707 inches

**Shoulder Diameter:**

Between 0.993 inches and 0.998 inches

**Shoulder Length:**

2.375 inches

**Ring Stock Diameter:**

Between 0.667 inches and 0.707 inches

**Thread Diameter:**

0.750 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Material:**

Steel comp 4340 and steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-8503 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response

**Surface Treatment:**

Cadmium and chromate or zinc

**Surface Treatment Specification:**

Qq-p-416 ty2cl3 federal specification 1st treatment response or qq-p-325 ty2cl3 federal specification 2nd treatment response

**Style Designator:**

Swivel

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1251 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.