NSN 5306-01-437-5526

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-437-5526

Thread	Class
Inteau	UIA33 .

3a

Thread Direction:

Right-hand

Thread Length:

0.735 inches

Fastener Length:

Between 1.470 inches and 1.500 inches

Head Style:

Dished hexagon

Head Height:

0.250 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Grip Diameter:

Between 0.4985 inches and 0.4995 inches

Thread Diameter:

0.500 inches

Grip Length:

Between 0.740 inches and 0.760 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-60422 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qqp-416 ty2cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6608 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5306-01-437-5526

Shear Bolt - Page 2 of 2

Fiig: A003b0

Mil-std (military Standard):

Mil-s-5000 spec.

