## NSN 5306-01-437-6091

Shear Bolt - Page 1 of 2

**Thread Class:** 

Right-hand **Thread Length:**0.484 inches

**Thread Direction:** 

Fastener Length:

Spline extended washer

**Head Style:** 

Between 1.344 inches and 1.374 inches

За



View Online at https://aerobasegroup.com/nsn/5306-01-437-6091

Head Height:
Between 0.240 inches and 0.260 inches
Extended Washer Diameter:
Between 0.460 inches and 0.470 inches
Extended Washer Thickness:
0.036 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Head Minor Diameter:
Between 0.235 inches and 0.250 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Minimum Yield Strength:
108000 pounds per square inch
Surface Finish:
32.0 microinches grip
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-437-6091

Shear Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0