NSN 5306-01-438-4867

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-438-4867 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** Between 1.610 inches and 1.640 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.235 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.465 inches and 0.475 inches **Extended Washer Thickness:** 0.042 inches **Hole Diameter:** Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **End Application:** B-1b **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.115 inches and 1.135 inches **Hole Quantity:** 4 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch **Hole Configuration Style:** Double hexagon flats **Special Features:** Requested name -tension bolt

Color:

Black threads

NSN 5306-01-438-4867

Shear Bolt - Page 2 of 2

Mil-c-85614 spec.



| Material: |
|--|
| Nickel alloy 718 |
| Material Specification: |
| Ams 5662 assn standard single material response |
| Surface Treatment: |
| Aluminum |
| Surface Treatment Specification: |
| Mil-c-85614 military specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| Mil-std (military Standard): |