NSN 5306-01-438-4869

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-438-4869

Thread Class: 3a **Thread Direction: Right-hand Thread Length:** 0.500 inches Fastener Length: Between 1.687 inches and 1.689 inches Head Style: Double hexagon extended washer **Head Height:** 0.235 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.465 inches and 0.475 inches **Extended Washer Thickness:** 0.042 inches Hole Diameter: Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **End Application:** B-1b **Thread Diameter:** 0.250 inches Grip Length: Between 1.178 inches and 1.198 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Double hexagon flats **Special Features:** Requested name -tension bolt Color: Black threads

NSN 5306-01-438-4869

Shear Bolt - Page 2 of 2



Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-c-85614 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-85614 spec.