NSN 5306-01-438-6562

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-438-6562

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.733 inches
Fastener Length: Between 1.530 inches and 1.560 inches
Head Style:
Double hexagon extended washer
Head Height:
0.375 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Extended Washer Diameter:
Between 0.740 inches and 0.750 inches
Extended Washer Thickness:
0.099 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
End Application:
B-1b
Thread Diameter:
0.4375 inches
Grip Length:
Between 0.802 inches and 0.822 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Double hexagon flats
Special Features:
Requested name-tension bolt
Color:

Black threads

NSN 5306-01-438-6562

Shear Bolt - Page 2 of 2

Mil-c-85614 spec.



Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Mil-c-85614 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):