

View Online at <https://aerobasegroup.com/nsn/5306-01-438-6562>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.733 inches

Fastener Length:

Between 1.530 inches and 1.560 inches

Head Style:

Double hexagon extended washer

Head Height:

0.375 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Extended Washer Diameter:

Between 0.740 inches and 0.750 inches

Extended Washer Thickness:

0.099 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

Between 0.4360 inches and 0.4370 inches

End Application:

B-1b

Thread Diameter:

0.4375 inches

Grip Length:

Between 0.802 inches and 0.822 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Double hexagon flats

Special Features:

Requested name-tension bolt

Color:

Black threads

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-c-85614 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-85614 spec.