NSN 5306-01-439-2507

Shear Bolt - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5506-01-459-2507
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.460 inches and 0.510 inches
Fastener Length:
Between 2.032 inches and 2.062 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.290 inches and 0.310 inches
Width Between Flats:
Between 0.306 inches and 0.315 inches
Extended Washer Diameter:
Between 0.428 inches and 0.439 inches
Extended Washer Thickness:
Between 0.059 inches and 0.079 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 1.552 inches and 1.572 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Product Name:
Navy special project
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification single material response or mil-s-6049 military specification single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas672 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-439-2507

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.