NSN 5306-01-440-6696

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-440-6696 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.355 inches and 0.395 inches **Fastener Length:** 0.625 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches **First Diameter From Head:** Between 0.200 inches and 0.206 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.280 inches and 0.320 inches **Thread Diameter:** 0.250 inches **Features Provided:** Washer Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project **Special Features:** Includes washer and wire rope Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response

N/a

Unjf

Shelf Life:

Thread Series Designator:

NSN 5306-01-440-6696

Externally Relieved Body Bolt - Page 2 of 2



Unit Of I	/leasure:
-----------	-----------

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.