NSN 5306-01-440-7560

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-440-7560 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.735 inches **Fastener Length:** Between 1.720 inches and 1.750 inches **Head Style:** Dished hexagon **Head Height:** Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Hole Diameter:** Between 0.070 inches and 0.080 inches **Washer Quantity: Thread Diameter:** 0.500 inches **Hole Quantity:** 3 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:** Hexagon corners **Primary Washer Outside Diameter:** 0.845 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.040 inches Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Cadmium and chromate

NSN 5306-01-440-7560

Assembled Washer Bolt - Page 2 of 2



Surface Treatment Speci

Qq-p-416, type 2, class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0