

View Online at <https://aerobasegroup.com/nsn/5306-01-442-4857>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Fastener Length:

Between 1.490 inches and 1.510 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.244 inches and 0.264 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

Extended Washer Diameter:

Between 0.465 inches and 0.475 inches

Extended Washer Thickness:

Between 0.032 inches and 0.052 inches

Hole Diameter:

Between 0.032 inches and 0.042 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Single Shear Strength:

132000 pounds per square inch

Thread Diameter:

0.250 inches

Grip Length:

1.000 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Nickel and cadmium and chromate

Surface Treatment Specification:

Ams 2416 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1785 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0