

View Online at <https://aerobasegroup.com/nsn/5306-01-442-5325>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.620 inches

**Fastener Length:**

1.855 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.171 inches and 0.191 inches

**Width Between Flats:**

Between 0.367 inches and 0.375 inches

**First Diameter From Head:**

Between 0.198 inches and 0.202 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.515 inches

**End Application:**

B-1b

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Item is made up of sleeve, lockwashe (ms35338-139) , flat washer, and spring helical compression: t.O. 12p1-4-33-1, fig 22, index 96:  
requested name-screw, radar trans

**Material:**

Stainless steel

**Material Specification:**

Mil-h-6875 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-h-6875 spec.