

View Online at <https://aerobasegroup.com/nsn/5306-01-442-5325>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.620 inches

Fastener Length:

1.855 inches

Head Style:

Hexagon

Head Height:

Between 0.171 inches and 0.191 inches

Width Between Flats:

Between 0.367 inches and 0.375 inches

First Diameter From Head:

Between 0.198 inches and 0.202 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.515 inches

End Application:

B-1b

Thread Diameter:

0.250 inches

Thread Qty Per Inch (tpi):

28

Externally Relieved Body Diameter Quantity:

1

Special Features:

Item is made up of sleeve, lockwashe (ms35338-139) , flat washer, and spring helical compression: t.O. 12p1-4-33-1, fig 22, index 96:
requested name-screw, radar trans

Material:

Stainless steel

Material Specification:

Mil-h-6875 military specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-h-6875 spec.