

View Online at <https://aerobasegroup.com/nsn/5306-01-442-7552>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.498 inches

Fastener Length:

Between 1.113 inches and 2.153 inches

Head Style:

Hexagon

Head Height:

Between 0.203 inches and 0.235 inches

Width Between Flats:

Between 0.553 inches and 0.565 inches

Shoulder Diameter:

0.371 inches first shoulder and 0.374 inches first shoulder

Shoulder Length:

1.625 inches first shoulder and 1.645 inches first shoulder

Thread Diameter:

0.312 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4037 or steel comp 4130 or steel comp 4140 or steel comp 8630 or steel comp 8735

Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-5626 military specification 3rd material response or mil-s-6050 military specification 4th material response or mil-s-6098 military specification 5th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas1297 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.