## NSN 5306-01-442-8352

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-442-8352
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.735 inches
Fastener Length:
Between 2.345 inches and 2.375 inches
Head Style:
Dished hexagon
Head Height:
Between 0.250 inches and 0.266 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Grip Diameter:
Between 0.4990 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 1.615 inches and 1.635 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response or ams 5853 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6708 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5306-01-442-8352

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0