

View Online at <https://aerobasegroup.com/nsn/5306-01-443-9914>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.041 inches

**Fastener Length:**

Between 1.338 inches and 1.368 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.375 inches and 0.390 inches

**Width Between Flats:**

Between 1.052 inches and 1.064 inches

**Locking Feature:**

Strip threads

**Grip Diameter:**

Between 0.7480 inches and 0.7490 inches

**Thread Diameter:**

0.750 inches

**Grip Length:**

Between 0.302 inches and 0.322 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp 4140 fastener or steel comp 4340 fastener or steel comp 8735 fastener or steel comp 8740 fastener or steel comp 6150 fastener

**Material Specification:**

Mil-s-5626 military specification 1st material response fastener or mil-s-5000 military specification 2nd material response fastener or mil-s-6098 military specification 3rd material response fastener or mil-s-6049 military specification 4th material response fastener or mil-s-8503 military specification 5th material response fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification all treatment responses fastener

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1231 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.