## NSN 5306-01-444-7489

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-444-7489
Thread Direction:
Right-hand
Thread Length:
Between 39.0 millimeters and 41.0 millimeters
Fastener Length:
Between 47.0 millimeters and 53.0 millimeters
Head Style:
Hexagon extended washer
Head Height:
15.5 millimeters
Width Between Flats:
Between 20.5 millimeters and 21.1 millimeters
Extended Washer Diameter:
32.8 millimeters
Extended Washer Thickness:
2.4 millimeters
Shoulder Diameter:
16.89 millimeters first shoulder and 17.00 millimeters first shoulder
Shoulder Length:
9.0 millimeters first shoulder and 11.0 millimeters first shoulder
Thread Diameter:
16.0 millimeters
Thread Pitch In Millimeters:
1.5
External Thread Tolerance Class:
6g
Shoulder Shape:
Round first shoulder
Material:
Steel property class 10.9
Material Specification:
Din 267, part 11 assn standard single material response or din 6921 assn standard single material response
Surface Treatment:
Zinc
Surface Treatment Specification:
Din 267, part 9 assn standard single treatment response
Test Data Document:
D8286-din 6921 standard (includes industry or association standards, individual manufactureer standards, etc.). And d8286-din 962
standard (includes industry or association standards, individual manufactureer standards, etc.).
Thread Series Designator:
M
Shalf Life:

N/a

## **NSN 5306-01-444-7489** Shoulder Bolt - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

Demilitarization:

No

Fiig:

A003b0