## NSN 5306-01-445-3710

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-445-3710 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.390 inches **Fastener Length:** Between 1.437 inches and 1.467 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.200 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.359 inches and 0.369 inches **Extended Washer Thickness:** 0.050 inches **Hole Diameter:** Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **End Application:** B-1b **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.052 inches and 1.072 inches **Hole Quantity:** 4 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch **Hole Configuration Style:** Double hexagon flats **Special Features:** 

Color:

Black threads

Requested name-tension bolt

## NSN 5306-01-445-3710

Shear Bolt - Page 2 of 2

Mil-c-85614 spec.



Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Mil-c-85614 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):