## NSN 5306-01-445-3711

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-445-3711 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** Between 1.297 inches and 1.327 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.235 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.465 inches and 0.475 inches **Extended Washer Thickness:** 0.042 inches **Hole Diameter:** Between 0.050 inches and 0.060 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **End Application:** B-1b **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.802 inches and 0.822 inches **Hole Quantity:** 4 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch **Hole Configuration Style:** Double hexagon flats **Special Features:** Requested name-tension bolts

Color:

Black threads

## NSN 5306-01-445-3711

Shear Bolt - Page 2 of 2

Mil-c-85614 spec.



Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Mil-c-85614 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):