

View Online at <https://aerobasegroup.com/nsn/5306-01-445-9597>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.877 inches

**Fastener Length:**

2.712 inches

**Head Style:**

Double hexagon

**Head Height:**

0.468 inches

**Width Between Flats:**

0.560 inches

**Washer Quantity:**

1

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**End Application:**

B-1b

**Thread Diameter:**

0.3750 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.360 inches first hole

**Primary Washer Outside Diameter:**

0.875 inches

**Primary Washer Style:**

Flat

**Primary Washer Material Thickness:**

0.070 inches

**Special Features:**

Item comes with expandable bushing, tab washer and nut: requested name - bolt, expand Irud af

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Lubricant

**Surface Treatment Specification:**

Mil-I-46010 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-I-46010 spec.