## NSN 5306-01-446-3143

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-446-3143

**Thread Class:** Aal **Thread Direction: Right-hand Thread Length:** 0.910 inches Fastener Length: Between 2.207 inches and 2.237 inches **Head Style:** Spline extended washer **Head Height:** Between 0.420 inches and 0.440 inches **Extended Washer Diameter:** Between 0.808 inches and 0.838 inches **Extended Washer Thickness:** Between 0.113 inches and 0.123 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches Head Minor Diameter: Between 0.637 inches and 0.651 inches **End Application:** Aircraft, stratofortress b-52 **Thread Diameter:** 0.500 inches Grip Length: Between 1.302 inches and 1.322 inches **Features Provided:** Dry film lubricant Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response

## NSN 5306-01-446-3143

Shear Bolt - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

