## NSN 5306-01-447-1228

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-447-1228

· · · · · · · · · · · · · · · · · · ·
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.454 inches
Fastener Length:
Between 1.939 inches and 1.969 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Grip Diameter:
Between 0.3740 inches and 0.3745 inches
Shank Unthreaded Hole Diameter:
0.106 inches threads and 0.116 inches threads
Thread Diameter:
0.375 inches
Grip Length:
Between 1.490 inches and 1.510 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.771 inches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams5737 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6306 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5306-01-447-1228

Shear Bolt - Page 2 of 2



Fiig:

A003b0