

View Online at <https://aerobasegroup.com/nsn/5306-01-447-7824>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.240 inches and 0.250 inches

Fastener Length:

Between 0.302 inches and 0.312 inches

Head Style:

Dished hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Hole Diameter:

Between 0.076 inches and 0.077 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

End Application:

F-15i

Thread Diameter:

0.250 inches

Grip Length:

Between 0.052 inches and 0.072 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Hexagon corners

Special Features:

Requested name-bolt: altered item made from nas1304-1h

Material:

Steel comp 4140 or steel comp 4340 or steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or ams 6415 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.