## NSN 5306-01-448-1931

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-448-1931

	<b>.</b> .
Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.528 inches

#### Fastener Length:

Between 2.388 inches and 2.418 inches

#### Head Style:

Dished hexagon

Head Height:

Between 0.250 inches and 0.265 inches

#### Width Between Flats:

Between 0.741 inches and 0.752 inches

#### Grip Diameter:

Between 0.4985 inches and 0.4995 inches

**Thread Diameter:** 

0.500 inches

Grip Length:

Between 1.865 inches and 1.885 inches

## Thready Qty Per Inch (tpi):

20

#### Min. Tensile Strength (psi):

95000 pounds per square inch

Material:

Titanium alloy uns r54520

#### **Material Specification:**

Ams4928 military specification 1st material response or ams4967 military specification 2nd material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Nas4006 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas6408 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5306-01-448-1931

Shear Bolt - Page 2 of 2

Fiig: A003b0

Mil-std (military Standard):

spec.

