## NSN 5306-01-448-1931

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-448-1931 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.528 inches **Fastener Length:** Between 2.388 inches and 2.418 inches **Head Style:** Dished hexagon **Head Height:** Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.865 inches and 1.885 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 95000 pounds per square inch Material: Titanium alloy uns r54520 **Material Specification:** Ams4928 military specification 1st material response or ams4967 military specification 2nd material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas4006 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6408 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5306-01-448-1931

Shear Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

spec.