## NSN 5306-01-448-2157



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-448-2157 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.454 inches **Fastener Length:** Between 3.064 inches and 3.094 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 2.615 inches and 2.635 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Steel comp 4340 or steel comp 8740

**Material Specification:** 

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 1st material response

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

**Specification Data:** 

80205-nas6202 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5306-01-448-2157

Shear Bolt - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.