NSN 5306-01-448-8662



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-448-8662 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.877 inches and 0.927 inches **Fastener Length:** Between 2.762 inches and 2.792 inches **Head Style:** Dished hexagon **Head Height:** Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches **Grip Diameter:** Between 0.623 inches and 0.624 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 1.865 inches and 1.885 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization:

NSN 5306-01-448-8662

Shear Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.