

View Online at <https://aerobasegroup.com/nsn/5306-01-448-8666>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.425 inches

Fastener Length:

Between 0.972 inches and 1.002 inches

Head Style:

Dished hexagon

Head Height:

0.125 inches

Width Between Flats:

Between 0.429 inches and 0.439 inches

Locking Feature:

Patch threads

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 0.552 inches and 0.572 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Minimum Yield Strength:

95000 pounds per square inch

Surface Finish:

32.0 microinches grip

Material:

Plastic polyamide locking feature

Material Specification:

Ams5731 assn standard 1st material response or ams5737 assn standard 2nd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6704 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0