NSN 5306-01-448-9036

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-448-9036 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.159 inches and 1.209 inches **Fastener Length:** Between 3.369 inches and 3.399 inches **Head Style:** Dished hexagon **Head Height:** Between 0.438 inches and 0.453 inches Width Between Flats: Between 1.239 inches and 1.252 inches **Grip Diameter:** Between 0.8730 inches and 0.8740 inches **Thread Diameter:** 0.875 inches **Grip Length:** Between 2.615 inches and 2.635 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6614 professional/industrial association standard Shelf Life:

N/a

NSN 5306-01-448-9036

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.