NSN 5306-01-449-1150

Shear Bolt - Page 1 of 2

Thread Class:





3a **Thread Direction: Right-hand Thread Length:** 0.818 inches Fastener Length: Between 2.553 inches and 2.583 inches **Head Style:** Spline extended washer **Head Height:** Between 0.040 inches and 0.060 inches **Extended Washer Diameter:** Between 0.922 inches and 0.932 inches **Extended Washer Thickness:** Between 0.062 inches and 0.082 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches Head Minor Diameter: Between 0.547 inches and 0.562 inches **Thread Diameter:** 0.500 inches Grip Length: Between 1.740 inches and 1.760 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5306-01-449-1150

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

