## NSN 5306-01-450-0725

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-450-0725 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.925 inches and 0.975 inches **Fastener Length:** Between 3.185 inches and 3.215 inches **Head Style:** Spline extended washer **Head Height:** Between 0.495 inches and 0.515 inches **Extended Washer Diameter:** Between 1.037 inches and 1.047 inches **Extended Washer Thickness:** Between 0.071 inches and 0.091 inches **Grip Diameter:** Between 0.5605 inches and 0.5615 inches **Head Minor Diameter:** Between 0.610 inches and 0.625 inches **Thread Diameter:** 0.562 inches **Grip Length:** Between 2.250 inches and 2.260 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches grip

Material:

Steel comp h11

**Material Specification:** 

Ams 6487 assn standard single material response

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Mil-c-8837 type 2 cl 2 military specification single treatment response

**Thread Series Designator:** 

Unjf

## NSN 5306-01-450-0725

Close Tolerance Bolt - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-c-8837 spec.