Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-450-3254

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.747 inches and 0.757 inches
Fastener Length:
Between 1.658 inches and 1.668 inches
Head Style:
Flat fillister
Head Diameter:
Between 0.620 inches and 0.630 inches
Head Height:
Between 0.502 inches and 0.512 inches
Shoulder Diameter:
Between 0.557 inches and 0.567 inches
Shoulder Length:
Between 0.846 inches and 0.856 inches
Concentric Hole Diameter:
Between 0.339 inches and 0.349 inches
Thread Diameter:
0.500 inches
Thread Series:
Unc counterbore
Nonstandard Thread Pitch Diameter:
+0.4448/+0.4500 inches
Thready Qty Per Inch (tpi):
13
Material:
Steel comp 303
Material Specification:
Astm a276, a479, a581, or a582 assn standard single material response
Surface Treatment Specification:
Mil-std-171, para 5.4.1, dimensional limits apply after finish military standard single treatment response
Style Designator:
Counterbore threaded
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
-

Internally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-std-171 spec.