NSN 5306-01-451-7370

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-451-7370

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.175 inches |
| Fastener Length: |
| 4.050 inches |
| Head Style: |
| Double hexagon extended washer |
| Head Height: |
| 0.808 inches |
| Width Between Flats: |
| Between 0.928 inches and 0.940 inches |
| Extended Washer Diameter: |
| 1.433 inches |
| Extended Washer Thickness: |
| 0.198 inches |
| Grip Diameter: |
| Between 0.8735 inches and 0.8740 inches |
| Thread Diameter: |
| 0.875 inches |
| Grip Length: |
| 2.875 inches |
| Thready Qty Per Inch (tpi): |
| 14 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams5662 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unif |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| UIII UI WEASUIE. |

NSN 5306-01-451-7370

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0