# NSN 5306-01-452-4836

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-452-4836

Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.908 inches

#### Fastener Length:

1.283 inches

#### Head Style:

Spline extended washer

#### Head Height:

Between 0.440 inches and 0.460 inches

#### **Extended Washer Diameter:**

Between 0.922 inches and 0.932 inches

#### **Extended Washer Thickness:**

Between 0.062 inches and 0.082 inches

#### Hole Diameter:

Between 0.045 inches and 0.065 inches

#### **Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

### Head Minor Diameter:

Between 0.547 inches and 0.562 inches

### Thread Diameter:

0.500 inches

#### Grip Length:

Between 0.365 inches and 0.385 inches

#### Hole Quantity:

4

Hole Type:

Drilled

#### Thready Qty Per Inch (tpi):

20

# Min. Tensile Strength (psi):

180000 pounds per square inch

# Hole Configuration Style:

Double hexagon flats

# Material:

Nickel alloy 718

# Material Specification:

Ams 5662 assn standard single material response

## Surface Treatment:

Passivate

# NSN 5306-01-452-4836

Shear Bolt - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0