

View Online at <https://aerobasegroup.com/nsn/5306-01-453-9479>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.735 inches

Fastener Length:

Between 7.720 inches and 7.750 inches

Head Style:

Dished hexagon

Head Height:

Between 0.250 inches and 0.265 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Locking Feature:

Pellet fastener or patch fastener or strip fastener

Grip Diameter:

Between 0.4990 inches and 0.4995 inches

Thread Diameter:

0.500 inches

Grip Length:

Between 6.990 inches and 7.010 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Plastic locking feature

Material Specification:

Ams5731 assn standard single material response fastener or ams5732 assn standard single material response fastener or ams5737 assn standard single material response fastener or ams5853 assn standard single material response fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas6708 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0