

View Online at <https://aerobasegroup.com/nsn/5306-01-454-0318>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.590 inches

Fastener Length:

Between 2.490 inches and 2.510 inches

Head Style:

Hexagon

Head Height:

Between 0.378 inches and 0.403 inches

Width Between Flats:

Between 0.922 inches and 0.938 inches

Grip Diameter:

Between 0.623 inches and 0.624 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.625 inches

Grip Length:

Between 1.900 inches and 1.920 inches

Thready Qty Per Inch (tpi):

11

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.380 inches first hole

Surface Finish:

32.0 microinches grip

Special Features:

Surface treatment: alumizite "z" supplied by tiodize, cage 34568

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-c-85614 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-85614 spec.