## NSN 5306-01-454-8972

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-454-8972

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.659 inches
Fastener Length:
Between 2.169 inches and 2.199 inches
Head Style:
Spline extended washer
Head Height:
Between 0.327 inches and 0.347 inches
Extended Washer Diameter:
Between 0.691 inches and 0.701 inches
Extended Washer Thickness:
Between 0.044 inches and 0.064 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Head Minor Diameter:
Between 0.423 inches and 0.438 inches
End Application:
F/a-18e aircraft
Thread Diameter:
0.3750 inches
Grip Length:
Between 1.490 inches and 1.510 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Criticality Code Justification:
Agav
Surface Finish:
32.0 microinches bearing surface of head
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response or ams 5663 assn standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unjf

## NSN 5306-01-454-8972

Shear Bolt - Page 2 of 2



he			

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0