

View Online at <https://aerobasegroup.com/nsn/5306-01-455-1401>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.037 inches and 1.070 inches

**Fastener Length:**

Between 1.250 inches and 1.312 inches

**Head Style:**

Crowned hexagon

**Head Height:**

0.203 inches

**Width Between Flats:**

Between 0.553 inches and 0.563 inches

**Hole Diameter:**

Between 0.069 inches and 0.074 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.031 inches and 0.062 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hole Configuration Style:**

Hexagon longitudinal hole

**Special Features:**

Slot located at thread end

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 4037 or steel comp 4130

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas428 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0