Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-455-3780

Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
0.770 inches
Fastener Length:
6.590 inches
Head Style:
Hexagon extended washer
Head Height:
1.320 inches
Width Between Flats:
Between 1.812 inches and 1.875 inches
Extended Washer Diameter:
2.250 inches
Extended Washer Thickness:
0.250 inches
Locking Feature:
Pellet threads
Point Diameter:
Between 1.134 inches and 1.144 inches
First Diameter From Head:
Between 1.370 inches and 1.380 inches
Second Diameter From Head:
Between 1.499 inches and 1.500 inches
Third Diameter From Head:
1.375 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.060 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
4.940 inches
Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
6.590 inches
Point Style:
Flat
Thread Diameter:
1.375 inches
Thready Qty Per Inch (tpi):
6
Externally Relieved Body Diameter Quantity:
3
•

NSN 5306-01-455-3780

Externally Relieved Body Bolt - Page 2 of 2



Point Chamfer Angle:

45.0 degrees

Material:

Plastic polyamide locking feature

Material Specification:

Qq-n-286 form 2 cond anl, ah, fin-a federal specification single material response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0