
NSN 5306-01-455-6332

Machine Bolt - Page 1 of 2



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** 0.908 inches Fastener Length: Between 2.643 inches and 2.673 inches **Head Style:** Spline extended washer **Head Height:** 0.450 inches **Extended Washer Diameter:** Between 0.922 inches and 0.932 inches **Extended Washer Thickness:** Between 0.062 inches and 0.082 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches Head Minor Diameter: Between 0.642 inches and 0.651 inches **Thread Diameter:** 0.500 inches Grip Length: Between 1.740 inches and 1.760 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Minimum Yield Strength: 125000 pounds per square inch Surface Finish: 32.0 microinches fastener Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response



NSN 5306-01-455-6332

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

