
Machine Bolt - Page 1 of 2

3a

18



**Thread Class: Thread Direction: Right-hand Thread Length:** 1.071 inches Fastener Length: Between 3.581 inches and 3.611 inches **Head Style:** Spline extended washer **Head Height:** Between 0.552 inches and 0.572 inches **Extended Washer Diameter:** Between 1.153 inches and 1.163 inches **Extended Washer Thickness:** Between 0.080 inches and 0.100 inches **Grip Diameter:** Between 0.623 inches and 0.624 inches Head Minor Diameter: Between 0.776 inches and 0.782 inches Thread Diameter: 0.625 inches Grip Length: Between 3.518 inches and 3.548 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch Minimum Yield Strength: 125000 pounds per square inch Surface Finish: 32.0 microinches fastener Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response



## NSN 5306-01-455-6333

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

