NSN 5306-01-456-8438

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-456-8438

| View Online at https://aerobasegroup.com/nsn/5306-01-456-8 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.718 inches and 0.768 inches |
| Fastener Length: |
| Between 2.416 inches and 2.446 inches |
| Head Style: |
| Spline extended washer |
| Head Height: |
| Between 0.383 inches and 0.403 inches |
| Extended Washer Diameter: |
| Between 0.807 inches and 0.817 inches |
| Extended Washer Thickness: |
| Between 0.053 inches and 0.073 inches |
| Grip Diameter: |
| Between 0.4360 inches and 0.4370 inches |
| Head Minor Diameter: |
| Between 0.514 inches and 0.521 inches |
| Thread Diameter: |
| 0.438 inches |
| Grip Length: |
| Between 1.678 inches and 1.698 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches grip |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams 5662 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |

N/a

NSN 5306-01-456-8438

Shear Bolt - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0