NSN 5306-01-457-8558

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-457-8558

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.840 inches |
| Fastener Length: |
| Between 2.200 inches and 2.230 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.281 inches and 0.296 inches |
| Width Between Flats: |
| Between 0.865 inches and 0.877 inches |
| Grip Diameter: |
| Between 0.5610 inches and 0.5615 inches |
| Shank Unthreaded Hole Diameter: |
| 0.106 inches first hole and 0.116 inches first hole |
| Thread Diameter: |
| 0.562 inches |
| Grip Length: |
| Between 1.365 inches and 1.385 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 1.183 inches first hole and 1.188 inches first hole |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas6809 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5306-01-457-8558

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0