

View Online at <https://aerobasegroup.com/nsn/5306-01-458-3586>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.777 inches

Fastener Length:

Between 3.012 inches and 3.042 inches

Head Style:

Spline drive shear head

Head Height:

0.350 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Shank Unthreaded Hole Diameter:

0.146 inches first hole and 0.151 inches first hole

Head Minor Diameter:

Between 0.922 inches and 0.954 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 2.240 inches and 2.260 inches

Thread Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

260000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.854 inches first hole

Surface Finish:

32.0 microinches grip

Material:

Cobalt alloy mp-159

Material Specification:

Ams5842 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0