## NSN 5306-01-458-6618

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-458-6618 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.705 inches **Fastener Length:** Between 2.128 inches and 2.158 inches **Head Style:** Spline extended washer **Head Height:** Between 0.383 inches and 0.403 inches **Extended Washer Diameter:** Between 0.807 inches and 0.817 inches **Extended Washer Thickness:** Between 0.053 inches and 0.073 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches **Head Minor Diameter:** 0.514 inches **Thread Diameter:** 0.437 inches **Grip Length:** Between 1.428 inches and 1.448 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 22000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5306-01-458-6618

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0