NSN 5306-01-458-9650

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-458-9650 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.009 inches **Fastener Length:** Between 6.556 inches and 6.586 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.701 inches and 0.721 inches Width Between Flats: Between 0.803 inches and 0.814 inches **Extended Washer Diameter:** Between 1.220 inches and 1.230 inches **Extended Washer Thickness:** 0.178 inches **Grip Diameter:** Between 0.7485 inches and 0.7490 inches **Thread Diameter:** 0.750 inches **Grip Length:** Between 5.552 inches and 5.572 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches grip Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-01-458-9650

Shear Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0